

INVERTER STARTER 100kVA

P/N: Q729

DESCRIPTION: INVERTER STARTER

NOMINAL POWER: 100 kVA

INPUT LINE: 450/900 V DC

OUTPUT LINE: THREE-PHASE 380V 180Hz (current 150A)

DIMENSIONS & MASS: WDH [mm] 600x500x1200
(without resilient)
MAX 250 Kg

MAIN PROJECT STANDARDS REFERENCES:

- MIL-STD-810 (Environmental conditions)
- MIL-STD-461 (EMC)*
- MIL-STD-167-1 (Vibration)*
- MIL-STD-740 (Noise)*
- MIL-S-901 (Shock)

* Test performed by laboratory

COOLING SYSTEM: FORCED AIR AND DISTILLATE WATER

IP GRADE: IP54

ELECTRIC INTERFACE: MIL CONNECTORS

SYSTEM (e.g.)

AC MOTOR STARTER FOR BILGE PUMP

APPLICATION FIELD: NAVAL DEFENCE

KEY POINT: LOW AIRBORNE & STRUCTUREBORNE NOISE



Eurocontrol S.p.A., società a socio unico

Via Luigi Cibrario, 4 - 16154 Genova | Tel. +39 010 42 25 11
info@eurocontrol-spa.com | www.eurocontrol-spa.com

