

HYDRAULIC PUMP MOTOR DRIVE

P/N: Q722
DESCRIPTION: STAR DELTA DOUBLE STARTER
NOMINAL POWER: 90kW

INPUT LINE

2 PARALLEL LINES MANUALLY SELECTABLE
LINE IN 1: 3ph 440V @60 HZ
LINE IN 2: 3ph 440V @60 HZ

OUTPUT LINE

LINE OUT 1: 90kW Motor A
LINE OUT 2: 90kW Motor B
LINE OUT 3: 5,5kW Motor

DIMENSIONS & MASS: WDH [mm] 500x350x1100
(without resilient)
MAX 135 Kg

PROJECT STANDARDS REFERENCES:

- MIL-STD-810 (Environmental conditions)
- MIL-STD-461 (EMC)
- MIL-STD-167-1 (Vibration)
- MIL-STD-740 (Noise)
- MIL-S-901 (Shock)

COOLING SYSTEM: FORCED AIR
IP GRADE: IP54
ELECTRIC INTERFACE: TERMINAL BOARDS & GLANDS

SYSTEM
HYDRAULIC PUMP WITH CONSTANT SPEED AND SOFT STARTER

APPLICATION FIELD: NAVAL DEFENCE

KEY POINT: LOW MAGNETIC SIGNATURE

