

ELECTRO OPTICAL DIRECTOR (EOD)

P/N: M332

DESCRIPTION: DIRECT DRIVE EOD

SYSTEM COMPONENTS

- Q573 EOD CONTROL UNIT
- M332 EOD equipped with
- M324 DAY CAMERA WITH ZOOM 10X
- IR camera and LRF (model TBD)

INPUT LINE: 90Vdc (other voltage on request)

STABILIZATION ERROR: base $\leq 0,1$ mrad
peak $\leq 0,3$ mrad

SPEEDS AND ACCELERATIONS:

ELEVATION MAX SPEED 115°/s

ELEVATION MAX ACC 500°/s²

BEARING MAX SPEED 135°/s

BEARING MAX ACC 1000°/s²

COMMUNICATION SYSTEM:RS422 CONNECTION

AZIMUTH ANGLE RANGE: -20° +70°

TRAINING ANGLE RANGE: -172° + 172°

DIMENSIONS & MASS: [mm] 610 x 400 x 340
62 Kg

MAIN PROJECT STANDARDS REFERENCES:

- MIL-STD-810 (Environmental conditions) *
- MIL-STD-461 (EMC) *
- MIL-STD-740 (Noise)
- Limited MIL-S- 901 (Shock) *
- MIL-STD-167-1 (Vibration) *

*Test performed by Certified Laboratory

IP GRADE: IP65

ELECTRIC INTERFACE: MIL CONNECTORS

SYSTEM (e.g.):

SURVEILLANCE

TRACKING SYSTEM

FIRE COMMAND SYSTEM

APPLICATION FIELD: NAVAL DEFENCE

KEY POINT: MULTISENSORS OPTION, LOW ERROR DURING STABILIZATION



Eurocontrol S.p.A., società a socio unico

Via Luigi Cibrario, 4 - 16154 Genova | Tel. +39 010 42 25 11

info@eurocontrol-spa.com | www.eurocontrol-spa.com

